

355 SERIES

Rear Combination Lamps



Part#	Description	EAN Code
355ARWML	Stop/Tail/Indicator/Reverse/Reflector, Chrome, Left, Boxed	9335962036264
355ARWMR	Stop/Tail/Indicator/Reverse/Reflector, Chrome, Right, Boxed	9335962036271
355ARWM-2	Stop/Tail/Indicator/Reverse/Reflector, Chrome, Pair, Blister	9335962036257
355BARWML	Stop/Tail/Indicator/Reverse/Reflector, Black, Left, Boxed	9335962036295
355BARWMR	Stop/Tail/Indicator/Reverse/Reflector, Black, Right, Boxed	9335962036301
355BARWM-2	Stop/Tail/Indicator/Reverse/Reflector, Black, Pair, Blister	9335962036288

Voltage	9-32V
Dimensions	356 x 86 x 35mm
IP rating	IP67
Warranty	5 Years
Cable	400mm (stripped-end)
Operating temperature	-30°C to +50°C
Current draw (13.8V / 28V)	Stop: 0.16A / 0.09A, Tail: 0.50A / 0.26A, Indicator: 0.39A / 0.22A, Reverse: 0.23A / 0.12A

ECE approval	Function	Approval#
	Tail (R7)	R1-E9-02.23749
	Stop (R7)	S1-E9-02.23749
	Indicator (R6)	2a-E9-01.23749
	Reverse (R23)	AR-E9-00.23749
	Reflector (R3)	IA-E9-02.23749

Wiring colour codes	BROWN: Tail [+]	YELLOW / GREEN: Indicator [+]
	RED: Stop [+]	WHITE: Earth [-]
	BLACK: Reverse [+]	

Mounting instructions

⚠ Installation to be undertaken by a competent professional

1. Drill two holes in the fixing surface for the bolts (116mm apart) and one centred between them for the cable.
2. Run wires through the cable hole and attach the lamp using the fixings provided.



Inactive - 355BARWML



Inactive - 355BARWMR



Inactive - 355ARWML



Inactive - 355ARWMR



Active - Left



Active - Right

