

## SQ4 Range (R65 Approved)



### Main Features

- SQ4A: 4 x 3W LEDs - Double flash meets R65
- Steady on function
- Supplied with single point fix adjustable mounting bracket
- Multiple units can be linked for synchronised / alternate flash
- Max. Current: 0.6A @ 12.8V / 0.3A @ 24V
- Polycarbonate lens with diecast housing



Part Number	Voltage	Colour	Flash Patterns	ECE R65
SQ4A	10-30V	Amber	5	✓
SQ4B	10-30V	Blue	18	-
SQ4R	10-30V	Red	18	-
SQ4W	10-30V	White	18	-

## Hideaway Range



**SM3**  
Ø46.7 x 17mm (D)



**RM3**  
Ø36 x 39mm (D)



**LAP9169X**  
Ø40 x 33.4mm (D)



**LAP9170X**  
Ø43.3 x 26.1mm (D)

Part Number	Voltage	Colour	Number of LEDs	ECE R65	Connector	IP Rating	Flash Patterns	Current @ 12V / 24V
SM3A	10-30V	Amber	3	-	-	IP67	12	0.5A / 0.2A
SM3B	10-30V	Blue	3	-	-	IP67	12	0.5A / 0.2A
RM3A	10-30V	Amber	3	✓	-	IP65	16	0.5A / 0.2A
RM3B	10-30V	Blue	3	✓	-	IP65	16	0.5A / 0.2A
LAP9169X	10-30V	Amber	9	-	✓	IP65	29	0.8A / 0.4A
LAP9170X	10-30V	Amber	6	-	✓	IP65	19	0.7A / 0.3A